BendixKing.




KT 74

Mode S ADS-B Out enabled transponder ADS-B certified solutions

Solid State Slide-In Replacement ADS-B Transponder



- **Option 1:** Already have a compliant WAAS GPS? Add the KT 74 Transponder for ADS-B OUT.
- **Option 2:** Already have a compliant WAAS GPS and also want ADS-B Weather & Traffic*? Add the KGX 130R Certified ADS-B Receiver.
- **Option 3:** Need a compliant WAAS GPS source for ADS-B OUT? Add the KGX 150R Receiver with ADS-B Traffic and Weather* and an integrated WAAS GPS.









KT 74 Mode S ADS-B Transponder

The KT 74 brings simplicity, reliability and value into the cockpit that BendixKing has been trusted for since 1959. This ADS-B OUT compliant Mode S KT 74 Transponder offers a sleek design, low power consumption, a stop watch, a built in altitude monitor and repeater at an affordable price.

- Sleek design
- Low power consumption
- Stopwatch and timer
- Altitude monitor
- Built-in serial altitude repeater
- TIS Traffic output
- Certified ADS-B OUT for improved situational awareness

Designed for Next Generation requirements, the KT 74 meets global mandates for Automatic Dependent Surveillance-Broadcast (ADS-B). It is also a plug and play, slide-in replacement for the BendixKing KT 76A/C and KT 78A transponders (additional wiring for ADS-B compliance is needed).

Specifications	
Туре	Class 1 Mode S Level 2 els
Certification	ETSO C112d, TSO C112d; Class 1 Level 2 els ETSO C166b, TSO C166b; Class B1S
Compliance	EUROCAE ED-73E, EUROCAE ED-14G (RTCA DO-160G), RTCA DO-181E, RTCA DO-260B Corrigenda 1 DO-254B Level C
Supply Voltage (DC)	11-33 VDC
Operating Temperature	-13 to 158°F (-25 to +70°C)
Weight	2.8 lbs (1.35 kg)
Dimensions	1.7" (43mm) H x 6.30" (160mm) W x 10.7" (272mm) L

Find Out More To learn more, call 1.855.250.7027, contact your local BendixKing dealer or visit **bendixking.com BendixKing** 9201-B San Mateo Blvd. NE